

Technical Data Sheet [TDS]

AAT-167 Carpet Pad Adhesive

AAT-167 is a latex-resin base adhesive for fastening all types of padding: foam, jute, hair, synthetic fiber, rubberized felt, sponge rubber, and urethanes (primes or rebonds). AAT-167 fastens padding to most any surface: wood, concrete, metal deck, terrazzo, ceramic, or floor tiles.

Uses:

AAT-167 should be applied as follows:

- A. The floor must be clean, dry, and free of dust, dirt, grease, or oil.
- B. There is an inner seal under the screw cap of the container.
- C. Pour adhesive on the floor in a bead approx. 4" from the wall and then zig zag bead over the entire floor.
- D. Spread adhesive thin with scrap piece of carpet.
- E. Allow the adhesive to dry for 5 minutes and then roll pad into exact position required.

Specific Technical Data:

- A. Base Latex
- B. Color Tan
- C. Flammability Non-Flammable
- D. Clean-up Use AAT-197 to remove adhesive spills or for clean-up
- E. Shelf-Life One year from date of manufacture in an unopened container
- F. Freeze/Thaw Stable If frozen allow to thaw at room temperature. DO NOT agitate or stir while frozen.
- G. Packaging Size One Gallon, four per case

September 18, 2020



Printing date 09/18/2020 Reviewed on 09/18/2020

1 Identification

· Product identifier

Trade name: AAT-167 Pad Adhesive

Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Advanced Adhesive Technologies, LLC.

424 S Spencer St Dalton, GA 30721 Tel: 800-228-4583 Fax: 706-278-6207

· Emergency telephone number:

CHEMTREC USA +1 (800) 424-9300 & INTERNATIONAL +1 (703) 527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS07 GHS08

- · Signal word Warning
- · Hazard-determining components of labeling:

1,2-benzisothiazol-3(2H)-one

ethyl acrylate

· Hazard statements

May cause an allergic skin reaction.

Suspected of causing cancer.

Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

(Contd. on page 2)



Printing date 09/18/2020 Reviewed on 09/18/2020

Trade name: AAT-167 Pad Adhesive

(Contd. of page 1)

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- · NFPA ratings (scale 0 4)



Health = 0 Fire = 1 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0 Fire = 1 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
1332-58-7	Kaolin	40.68%
471-34-1	calcium carbonate	5.3%
140-88-5	ethyl acrylate	0.7%
2634-33-5	1,2-benzisothiazol-3(2H)-one	0.06%

4 First-aid measures

- Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.

(Contd. on page 3)



Printing date 09/18/2020 Reviewed on 09/18/2020

Trade name: AAT-167 Pad Adhesive

(Contd. of page 2)

- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

· PAC-1:		
64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	140 mg/m ³
471-34-1	calcium carbonate	45 mg/m³
140-88-5	ethyl acrylate	8.3 ppm
57-13-6	urea	30 mg/m³
141-43-5	2-aminoethanol	6 ppm
· PAC-2:		
64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	1,500 mg/m
471-34-1	calcium carbonate	210 mg/m ³
140-88-5	ethyl acrylate	36 ppm
57-13-6	urea	280 mg/m ³
141-43-5	2-aminoethanol	170 ppm
· PAC-3:		
64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	8,900 mg/m
471-34-1	calcium carbonate	1,300 mg/m
140-88-5	ethyl acrylate	240 ppm
57-13-6	urea	1,700 mg/m
141-43-5	2-aminoethanol	1,000 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

(Contd. on page 4)



Printing date 09/18/2020 Reviewed on 09/18/2020

Trade name: AAT-167 Pad Adhesive

(Contd. of page 3)

- · Information about protection against explosions and fires:
- Keep respiratory protective device available.
- Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

1332-58-7 Kaolin

- PEL Long-term value: 15* 5** mg/m³
 - *total dust **respirable fraction
- REL Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
- TLV Long-term value: 2* mg/m³
 - E; as respirable fraction

471-34-1 calcium carbonate

- PEL Long-term value: 15* 5** mg/m³
 - *total dust **respirable fraction
- REL Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
- TLV TLV withdrawn

140-88-5 ethyl acrylate

- PEL Long-term value: 100 mg/m³, 25 ppm
 - Skin
- REL See Pocket Guide App. A
- TLV Short-term value: 61 mg/m³, 15 ppm Long-term value: 20 mg/m³, 5 ppm
- · Additional information: The lists that were valid during the creation were used as basis.
- Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)



(Contd. of page 4)

Printing date 09/18/2020 Reviewed on 09/18/2020

Trade name: AAT-167 Pad Adhesive

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye protection:** Goggles recommended during refilling.

9 Physical and chemical prope	erties
Information on basic physical and General Information	chemical properties
· Appearance: Form:	Fluid
Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. Undetermined.
· Flash point:	>112 °C (>233.6 °F)
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapor pressure:	Not determined.
· Density: · Relative density · Vapor density	Not determined. Not determined. Not determined.

(Contd. on page 6)



Printing date 09/18/2020 Reviewed on 09/18/2020

Trade name: AAT-167 Pad Adhesive

(Contd. of page 5)

· Evaporation rate Not determined. · Solubility in / Miscibility with Water: Fully miscible. · Partition coefficient (n-octanol/water): Not determined. · Viscosity: Dynamic: Not determined. Kinematic: Not determined. · Solvent content: Organic solvents: 0.3 % Water: 22.3 % 0.30 % **VOC** content: 3.0 g/l / 0.03 lb/gal · Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:			
471-34-1 calcium carbonate			
Oral	LD50	6,450 mg/kg (rat)	
140-88-5 e	140-88-5 ethyl acrylate		
Oral	LD50	800 mg/kg (rat)	
Dermal	LD50	1,834 mg/kg (rabbit)	
Inhalative		2,180 mg/l (rat)	

- · Primary irritant effect:
- · on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

(Contd. on page 7)



Printing date 09/18/2020 Reviewed on 09/18/2020

Trade name: AAT-167 Pad Adhesive

(Contd. of page 6)

Carcinogenic categories

IARC (International Agency for Research on Cancer)

140-88-5 ethyl acrylate

2B

· NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · **Mobility in soil** No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

- · UN-Number
- · DOT, ADN, IMDG, IATA not regulated
- · UN proper shipping name
- · DOT, ADN, IMDG, IATA not regulated

(Contd. on page 8)



Printing date 09/18/2020 Reviewed on 09/18/2020

Trade name: AAT-167 Pad Adhesive

		(Contd. of page 7)
· Transport hazard class(es)		
· DOT, ADN, IMDG, IATA · Class	not regulated	
· Packing group · DOT, IMDG, IATA	not regulated	
· Environmental hazards:	Not applicable.	
· Special precautions for user	Not applicable.	
Transport in bulk according to Anne MARPOL73/78 and the IBC Code	x II of Not applicable.	
· UN "Model Regulation":	not regulated	

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· TS	SCA	(Toxic	Substances	Control Act):

All components have the value ACTIVE.

- · Hazardous Air Pollutants
- 140-88-5 ethyl acrylate
- · Proposition 65
- · Chemicals known to cause cancer:

140-88-5 ethyl acrylate

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA	(Environmental	Protection	Agency)
-------	----------------	------------	---------

57-13-6 urea

Ш

TLV (Threshold Limit Value established by ACGIH)

1332-58-7	Kaolin	A4
140-88-5	ethyl acrylate	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

140-88-5 ethyl acrylate

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).


(Contd. on page 9)



Printing date 09/18/2020 Reviewed on 09/18/2020

Trade name: AAT-167 Pad Adhesive

· Hazard pictograms







GHS07 GHS08

· Signal word Warning

· Hazard-determining components of labeling:

1,2-benzisothiazol-3(2H)-one ethyl acrylate

Hazard statements

May cause an allergic skin reaction.

Suspected of causing cancer.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Technical Department

· Contact: Technical Director

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent. Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2