

Technical Data Sheet [TDS]

AAT-722 Urethane Leveling Compound

AAT-722 is a two-part urethane, waterproof leveling compound. This high performance leveler is ideal for installations of a wide range of floorings over concrete slabs with very high moisture content. AAT-722 is also an effective moisture barrier for concrete sub-floors with up to 18#MVER and 97% in situ RH. The leveler can be applied from 1/32" up to 5". AAT adhesives can be applied directly to the leveler in as little as 4 hours. AAT-722 also provides crack bridging, STC and IIC properties.

The AAT-722 formula is solvent and water free, nonflammable, very low odor and is a certified "very low emission". The leveler is easy to spread, eliminates hollow spots, and remains flexible. The leveler is waterproof when cured, however, it is not a moisture inhibitor beyond the parameters stated below.

Prior to the start of the installation the installer must determine that the job-site conditions meet or exceed all applicable standards of the flooring manufacturer and AAT. Installation of any flooring should be one of the last jobs of any construction project. Sub-floors must be structurally sound. All dust, paint, varnish, oil, wax, finishes and any other bond inhibiting substances must be removed. Concrete sub-floors must be properly prepared according to the recommended practices detailed in the most recent version of document ASTM F-710. Depending upon type and condition of the sub-floor, a mechanical treatment [mechanical brushing, grinding or sanding] may be required. The extent of sub-floor prep can only be determined at the site by the installer. Clean the sub-floor with an industrial vacuum cleaner. Tack or damp mop the sub-floor before application of the leveling compound. Never sand existing resilient flooring that could contain asbestos. Follow all Federal, State and Local regulations relating to the removal of in-place, asbestos containing material.

AAT-722 Urethane Leveling Compound can be used over the following sub-floors. The AAT-722 can also serve as a moisture barrier when used over concrete sub-floors with a maximum moisture emission rate of 18lbs/1000 sq. ft. /24 hours [ASTM F1869] and a maximum in situ RH of 97% [ASTM F2170] @ a minimum of 1/32":

- Concrete above, on or below grade
- APA rated plywood underlayment
- OSB [underlayment grade]
- Existing non-cushion back resilient floors that are well bonded, sound, smooth, and free of waxes, finishes, cleaners and any other bond inhibiting substances.
- **Ceramic Tiles**
- Stone, Terrazzo
- Radiant heated sub-floors
- Asphalt
- Steel and aluminum
- Epoxy sealers [100% solid and fully cured]

For assistance with specific sub-floors please contact our Technical Services Department. AAT-722 cannot be used if adhesive removers, solvent or chemical cleaners have been used. For a copy of the Limited Warranty please contact Customer Service.

NOTE: Before beginning installations over sub-floors not listed contact AAT Technical Services for recommendations. AAT will not warrant the leveler when applied over Lauan plywood. AAT-722 cannot be used if adhesive removers, solvent or chemical cleaners have been used. Regulations may require that existing flooring material or coatings be tested to determine the asbestos content. Refer to the instructions for removal and handling of resilient flooring published by the RFCI in the publication, Recommended Work Practices for Removal of Resilient Floor Coverings. The Resilient Floor Covering Institute may be reached thru their Website www.rfci.org or by calling 301-340-8580.

Mixing of Components:

Pour 100% of part B [1.75 quart] into part A [2 gallons]. Mix thoroughly with an electric mixer for a minimum of three minutes or until a uniform mixture and color is achieved. Mixing ratio is 6.3 parts A to 1 part B by weight. Pot life is approximately 20 minutes at 70°F(21°C).

Installation Recommendations:

The installation site should have a consistent air temperature of 50°- 90°F and relative humidity levels should be 20% - 90% prior to the start of the installation. Higher temperatures will shorten pot life and drying time.

- 1. Refer to the information above for specific information regarding sub-floor preparation and site conditions. Spread the leveling compound with approximately 20 minutes.
- 2. Pour the leveling compound in a line 6-12 feet long and as close to the wet edge as possible.
- 3. Spread the compound to the desired thickness by raking through the compound with the appropriate notched trowel. Avoid placing the trowel directly in already spread areas as it may result in small puddles or droplets that may not flow out completely. The best results are achieved by moving in from a dry spot then passing through the leveler.
- 4. Finish by moving the trowel to another dry spot before lifting the trowel from the floor.
- 5. Release entrapped air approximately 30 minutes after raking by passing a spiked roller through the entire
- 6. Protect the leveling compound from direct sun and drafts during drying.

Trowel Recommendation:**

5/32" x 1/8" V notch [sawtooth] | up to 50 sf/gal. @ 1/32"

Note: Trowel Notch dimensions are Width x Depth x Separation

SPECIFIC TECHNICAL DATA:

- 1. VOC compliant, LEED qualified formula; no solvents, nonflammable
- 2. Compressive strength > 14,500psi
- 3. Clean-Up: Remove uncured leveler with acetone. Cured leveler will be difficult to remove, therefore, take care to remove leveler from unintended surfaces before it cures.
- 4. Packaging: Part A-2 gallon pail, Part B-1.75 quart
- 5. Shelf-Life: 24 months from date of manufacture in un-opened container when stored at 70°F.
- 6. Freeze-Thaw Stable

February 26, 2019



Reviewed on 01/24/2019 Printing date 01/24/2019

1 Identification

· Product identifier

· Trade name: AAT-722-A

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Advanced Adhesive Technologies LLC

424 South Spencer Street

Dalton, GA 30721 Tel: 800-228-4583 Fax: 706-278-6207

· Distributor:

Advanced Adhesive Technologies LLC

424 S Spencer St Dalton, GA 30721 Tel: 800-228-4583 Fax: 706-278-6207

2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified, according to the Globally Harmonized System (GHS).

- · Label elements
- · GHS label elements Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0Fire = 0Reactivity = 0

· WHMIS-ratings (scale 0 - 4)



Health = 0 Fire = 0

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

7727-43-7 barium sulphate, natural

50-100%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

Printing date 01/24/2019 Reviewed on 01/24/2019

Trade name: AAT-722-A

(Contd. of page 1)

4 First-aid measures

- Description of first aid measures
- · General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complications.
- After skin contact: Generally the product does not irritate the skin.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

| · PAC-1: | | | | |
|-----------|--------------------------|-----------------------|--|--|
| 7727-43-7 | barium sulphate, natural | 15 mg/m³ | | |
| 7664-38-2 | phosphoric acid | 3 mg/m³ | | |
| · PAC-2: | · PAC-2: | | | |
| 7727-43-7 | barium sulphate, natural | 170 mg/m³ | | |
| 7664-38-2 | phosphoric acid | 30 mg/m³ | | |
| · PAC-3: | | | | |
| 7727-43-7 | barium sulphate, natural | 990 mg/m³ | | |
| 7664-38-2 | phosphoric acid | 150 mg/m ³ | | |

- U:

Printing date 01/24/2019 Reviewed on 01/24/2019

Trade name: AAT-722-A

(Contd. of page 2)

7 Handling and storage

- Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

7727-43-7 barium sulphate, natural

PEL Long-term value: 15* 5** mg/m³

*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³

*total dust **respirable fraction

TLV Long-term value: 5* mg/m³

*inhalable fraction; E

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Wash hands before breaks and at the end of work.

- · Breathing equipment: Not necessary if room is well-ventilated.
- · Protection of hands: Not required.
- · Material of gloves Strong gloves
- · Eye protection: Goggles recommended during refilling.
- · Body protection: Protective work clothing

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information

· Appearance:

Form: Fluid

Color: According to product specification
• Odor: Characteristic

· Odor threshold:

· pH-value:

Not determined.

Not determined.

· Change in condition

Boiling point/Boiling range: 301 °C (573.8 °F)

(Contd. on page 4)

Printing date 01/24/2019 Reviewed on 01/24/2019

Trade name: AAT-722-A

(Contd. of page 3)

Flash point: Not applicable.
Flammability (solid, gaseous): Not applicable.
Ignition temperature: 420 °C (788 °F)
Decomposition temperature: Not determined.

· **Auto igniting:** Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard.

Not determined.

Not determined.

· Explosion limits:

Evaporation rate

Lower:

Upper:

Not determined.

Vapor pressure at 20 °C (68 °F):

Density:
Relative density
Vapor density
Not determined.
Not determined.
Not determined.
Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. Kinematic: Not determined.

· Solvent content:

VOC Content: 0.00 % 0.00 %

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect. · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

(Contd. on page 5)

Printing date 01/24/2019 Reviewed on 01/24/2019

Trade name: AAT-722-A

(Contd. of page 4)

· Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB**: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Smaller quantities can be disposed of with household waste.
- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · Environmental hazards:
- · Marine pollutant: No
- · Special precautions for user Not applicable.
- · Transport in bulk according to Annex II of
- MARPOL73/78 and the IBC Code Not applicable.

— u

Printing date 01/24/2019 Reviewed on 01/24/2019

Trade name: AAT-722-A

(Contd. of page 5)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

- · Section 313 (Specific toxic chemical listings):
- 7727-43-7 barium sulphate, natural
- 7664-38-2 phosphoric acid
- · TSCA (Toxic Substances Control Act):
- 7727-43-7 barium sulphate, natural
- 8001-79-4 Castor oil
- 7664-38-2 phosphoric acid
- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

- · Chemicals known to cause reproductive toxicity for females:
 - None of the ingredients is listed.
- · Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

- · Chemicals known to cause developmental toxicity:
- None of the ingredients is listed.
- Canadian Ingredient disclosure list
- · Limit 0,1%

None of the ingredients is listed.

· Limit 1%

None of the ingredients is listed.

- · Cancerogenity categories
- · EPA (Environmental Protection Agency)

7727-43-7 barium sulphate, natural

D, CBD(inh), NL(oral)

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · **Department issuing SDS:** Technical Department
- · Contact: Tel: 800-228-4583
- · Date of preparation / last revision 01/24/2019 / -



Printing date 01/24/2019 Reviewed on 01/24/2019

1 Identification

· Product identifier

· Trade name: AAT-722-B

- · Application of the substance / the mixture Hardening agent/ Curing agent
- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Advanced Adhesive Technologies LLC

424 South Spencer Street

Dalton, GA 30721 Tel: 800-228-4583 Fax: 706-278-6207

2 Hazard(s) identification

· Classification of the substance or mixture



GHS06 Skull and crossbones

Acute Tox. 1 H330 Fatal if inhaled.



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS06 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling: diphenylmethanediisocyanate,isomeres and homologues diphenylmethane-4,4'-di-isocyanante
- · Hazard statements

H330 Fatal if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

(Contd. on page 2)

Printing date 01/24/2019 Reviewed on 01/24/2019

Trade name: AAT-722-B

(Contd. of page 1)

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 If on skin: Wash with plenty of water.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

- Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 1 Reactivity = 0

· WHMIS-ratings (scale 0 - 4)



*3 Health = *3 Fire = 1 Reactivity = 0

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Substances
- CAS No. Description

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

- Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

| · Dangerous | Dangerous components: | | | | |
|-------------|-----------------------|---------------|---------------|----------------|--|
| 9016-87-9 d | iphenylmeth | anediisocyana | te,isomeres a | and homologues | |
| 40400 | | | | | |

50-100% 101-68-8 diphenylmethane-4,4'-di-isocyanante 25-50%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

Printing date 01/24/2019 Reviewed on 01/24/2019

Trade name: AAT-722-B

(Contd. of page 2)

· After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

· After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

Breathing difficulty

Coughing

Asthma attacks

- · Danger Danger of impaired breathing.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire fighting measures that suit the environment.

· Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Nitrogen oxides (NOx)

(Traces)

Hydrogen cyanide (HCN)

During heating or in case of fire poisonous gases are produced.

- Advice for firefighters
- · Protective equipment:

Wear fully protective suit.

Do not inhale explosion gases or combustion gases.

Mount respiratory protective device.

Wear self-contained respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Wear protective clothing.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)

Printing date 01/24/2019 Reviewed on 01/24/2019

Trade name: AAT-722-B

| Protective | Action Criteria for Chemicals | (Contd. of page 3 |
|------------|---|------------------------|
| PAC-1: | | |
| 9016-87-9 | diphenylmethanediisocyanate,isomeres and homologues | 0.15 mg/m ³ |
| 101-68-8 | diphenylmethane-4,4'-di-isocyanante | 0.45 mg/m ³ |
| PAC-2: | | · |
| 9016-87-9 | diphenylmethanediisocyanate,isomeres and homologues | 3.6 mg/m ³ |
| 101-68-8 | diphenylmethane-4,4'-di-isocyanante | 5 mg/m³ |
| PAC-3: | | |
| 9016-87-9 | diphenylmethanediisocyanate,isomeres and homologues | 22 mg/m³ |
| 101-68-8 | diphenylmethane-4,4'-di-isocyanante | 55 mg/m³ |

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Protect from frost.

Keep receptacle tightly sealed.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

PEL Ceiling limit value: 0.2 mg/m³, 0.02 ppm REL Long-term value: 0.05 mg/m³, 0.005 ppm

Ceiling limit value: 0.2* mg/m³, 0.02* ppm

*10-min

TLV Long-term value: 0.051 mg/m³, 0.005 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

(Contd. on page 5)

Printing date 01/24/2019 Reviewed on 01/24/2019

Trade name: AAT-722-B

(Contd. of page 4)

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

- · Protection of hands: Not required.
- · *Material of gloves* Butyl rubber, BR Nitrile rubber, NBR
- · As protection from splashes gloves made of the following materials are suitable: Natural rubber, NR
- · Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information

· Appearance:

Form: Fluid Color: Dark brown

Odor: Weak, characteristicOdor threshold: Not determined.pH-value: Not determined.

· Change in condition

Boiling point/Boiling range: Undetermined.
Setting temperature / range: 0 °C (32 °F)

Flash point: 201 °C (393.8 °F)
Flammability (solid, gaseous): Not applicable.
Ignition temperature: 400 °C (752 °F)
Decomposition temperature: Not determined.

· **Auto igniting:** Product is not selfigniting.

• **Danger of explosion:** Product does not present an explosion hazard.

· Explosion limits:

Lower: 0.4 Vol % Upper: Not determined.

· Vapor pressure at 20 °C (68 °F): 11 hPa (8.3 mm Hg)

Density at 20 °C (68 °F): 1.22 g/cm³ (10.1809 lbs/gal)

Relative density
 Vapor density
 Evaporation rate
 Not determined.
 Not determined.

(Contd. on page 6)

Printing date 01/24/2019 Reviewed on 01/24/2019

Trade name: AAT-722-B

(Contd. of page 5)

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic at 20 °C (68 °F): 220 mPas Kinematic: Not determined.

· Solvent content:

VOC Content: 0.00 % 0.00 %

Other information
 No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions

Reacts with water.

Exothermic reaction with amines and alcohols; reacts with water forming CO2; in closed containers, risk of bursting owing to increase of pressure.

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

| · LD/LC50 values that are relevant for classification: | | | |
|--|------|-------------------------|--|
| Oral | LD50 | >10,000 mg/kg (Ratte) | |
| Dermal | LD50 | >10,000 mg/kg (rabbit) | |
| Inhalative | LC50 | 0.493 mg/l (Ratte) (4h) | |

| | | 5 | |
|---|-----------|---|--|
| 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues | | | |
| Oral | LD50 | >2,000 mg/kg (Ratte) | |
| Dermal | LD50 | >9,400 mg/kg (rab) (OECD- Prüfrichtlinie 402) | |
| Inhalative | LC50/48 h | 490 mg/l (Ratte) (als Aerosol, Exposition) | |
| 101-68-8 diphenylmethane-4,4'-di-isocyanante | | | |
| Oral | LD50 | >2,000 mg/kg (Ratte) (Richtlinie 84/449/EWG, B.1) | |
| Dermal | LD50 | >9,400 mg/kg (rab) (OECD- Prüfrichtlinie 402) | |
| | | | |

- · Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization:

Sensitization possible through inhalation. Sensitization possible through skin contact.

Inhalative LC50/4h 0.368 mg/l (Ratte)

(Contd. on page 7)

Printing date 01/24/2019 Reviewed on 01/24/2019

Trade name: AAT-722-B

· Additional toxicological information:

(Contd. of page 6)

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

Very toxic

· Carcinogenic categories

| · IARC (Inte | · IARC (International Agency for Research on Cancer) | | | |
|---|--|---|--|--|
| 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues | | 3 | | |
| 101-68-8 | diphenylmethane-4,4'-di-isocyanante | 3 | | |
| · NTP (National Toxicology Program) | | | | |
| None of the ingredients is listed. | | | | |
| · OSHA-Ca (Occupational Safety & Health Administration) | | | | |
| None of the ingredients is listed. | | | | |

12 Ecological information

· Toxicity

| · Aquatic toxicity: | | | | | |
|--|--|--|--|--|--|
| LC0 | LC0 >1,000 mg/l (Fisch) (96h) | | | | |
| EC0 >500 mg/l (Daphnia magna Wasserfloh) (24h) | | | | | |
| | 1,640 mg/l (Scenedesmus subspicatus) (72h) | | | | |
| 9016-87- | 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues | | | | |
| LC0 | >1,000 mg/l (Fisch) (96h) | | | | |
| EC50 | EC50 >1,000 mg/l (Daphnia magna Wasserfloh) (OECD-Prüfrichtlinie 202) | | | | |
| 101-68-8 diphenylmethane-4,4'-di-isocyanante | | | | | |
| LC50/ 96 | h >1,000 mg/l (Danio rerio (Zebrabärbling)) (OECD- Prüfrichtlinie 203) | | | | |
| EC50 | >1,000 mg/l (Daphnia magna Wasserfloh) (OECD- Prüfrichtlinie 202) | | | | |
| NOEC | >10 mg/l (Daphnia magna Wasserfloh) (OECD- Prüfrichtlinie 202 (Fortpflanzung)) | | | | |

- Persistence and degradability Heavily biodegradable
- · Behavior in environmental systems:
- · Bioaccumulative potential Non significant accumulation in organisms
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

Printing date 01/24/2019 Reviewed on 01/24/2019

Trade name: AAT-722-B

(Contd. of page 7)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: If product has aged or solidified conventional means of disposal are acceptable.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· DOT, ADR, ADN, IMDG, IATA Void

UN proper shipping name

· DOT, ADR, ADN, IMDG, IATA Void

Transport hazard class(es)

· DOT, ADR, ADN, IMDG, IATA

· Class Void

· Packing group

· DOT, ADR, IMDG, IATA Void

· Environmental hazards:

· Marine pollutant: No

Special precautions for user Not applicable.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· UN "Model Regulation": Void

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

All ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 9)

Printing date 01/24/2019 Reviewed on 01/24/2019

Trade name: AAT-722-B

| Open adia a la puna dia ada ala puna liad | (Contd. of page 8) | |
|---|--------------------|--|
| · Canadian Ingredient disclosure list | | |
| · Limit 0,1% | | |
| 101-68-8 diphenylmethane-4,4'-di-isocyanante | | |
| · Limit 1% | | |
| None of the ingredients is listed. | | |
| · Cancerogenity categories | | |
| · EPA (Environmental Protection Agency) | | |
| 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues | CBD | |
| 101-68-8 diphenylmethane-4,4'-di-isocyanante | D, CBD | |
| · TLV (Threshold Limit Value established by ACGIH) | | |
| None of the ingredients is listed. | | |

· MAK (German Maximum Workplace Concentration)

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues 4 101-68-8 diphenylmethane-4,4'-di-isocyanante 4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · National regulations:
- · Technical instructions (air):

| Class | Share in % |
|-------|------------|
| I | 50-100 |

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · **Department issuing SDS:** Technical Department
- · Contact: Tel: 800-228-4583
- · Date of preparation / last revision 01/24/2019 / 105
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

Acute Tox. 1: Acute toxicity - Category 1

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2