

# Carpet Adhesives Quick Reference

BACKING TYPE	HEAVY COMMERCIAL TRAFFIC	LIGHT TO MID COMMERCIAL TRAFFIC	RESIDENTIAL TRAFFIC
<b>ActionBac or Jute</b> 1/8 x 1/8 x 1/8 U or Square Notch 90-110 sq. ft./gal. (commercial) 3/32 x 3/32 x 3/32 V or U 120-135 sq. ft./gal. (residential)	295, 299, 280, 275	275, 260, 230	230, 210, 188
<b>Latex Unitary</b> 1/8 x 1/8 x 1/16 U or or Square Notch 45-80 sq. ft./gal.	299, 295, 280, 275	PS*, 260, AB*	230
<b>Attached Urethane Cushion</b> (KangaBack®, KangaHyde®, KangaTrac®, System TR/18®, The Enhancer®) 3/32 x 3/32 x 3/32 U or V 120-135 sq. ft./gal. (residential)	299, 295, 280, 275	PS, 260, AB	230
<b>Hot Melt</b> 1/8 x 1/8 x 1/8 U or Square Notch 90-110 sq. ft./gal.	299, 295, 280, 275	PS, 260, AB	230
<b>Woven</b> 1/8 x 1/8 x 1/8 U 90-110 sq. ft./gal. (commercial) 1/8 x 1/8 x 1/8 V 100-120 sq. ft./gal. (residential)	299, 295, 280, 275	295, 280, 275	PS, 260
<b>Carpet Tile</b> 1/16 x 1/16 x 1/16 U 125-150 sq. ft./gal.	675, 332, 320	675, 332, 320	320
<b>PVC Six-Foot</b> 1/16 x 1/16 x 1/16 U or V 125-150 sq. ft./gal.	350	350	350
<b>Urethane Carpet Tile</b> (and all other non-vinyl backings) 1/32 x 1/16 x 1/32 U 180-250 sq. ft./gal.	675, 332, 320	320	370, 320
<b>Double Glue (cushion to floor)</b> 1/16 x 1/16 x 1/16 U or Square Notch 125-150 sq. ft./gal.	335, 332(r), 320(r), 280(p), 275(p)	335, 332(r), 320(r), PS(p)	335, 320(r), 260(p)
<b>Double Glue (carpet to cushion)</b> 1/8 x 1/8 x 1/16 (Spacer) U 45-80 sq. ft./gal.	299, 295, 280, 275	280, 275, PS	PS

(r) = releasable

(p) = permanent

PS = Problem Solver

AB = Anchor Bond

Typical trowel sizes recommended for these flooring products. Please refer to flooring manufacturer's specific recommendations.