

Wood & Ceramic Flooring Adhesives Quick Reference Guide

FLOORING TYPE	HEAVY COMMERCIAL TRAFFIC	MODERATE TO LIGHT COMMERCIAL	RESIDENTIAL TRAFFIC
Engineered Plank, Bamboo Plank 3/16 x 3/16 x 3/16 square notch 40-50 sq. ft./gal.	U.R.A., 2000	U.R.A., 2000	U.R.A., 2000
Engineered Plank, Thin Gauge Solid Plank* 3/16 x 1/4 x 5/16 V notch 50-60 sq. ft./gal.	*U.R.A., *2000	*U.R.A., *2000, EW	*U.R.A., *2000, EW
3/4" Solid Shorts, 1/2" Solid Plank* 3/16 x 3/16 x 3/16 square notch 40-50 sq. ft./gal.	U.R.A., 2000	U.R.A., 2000	U.R.A., 2000
Parquet Tile 1/8 x 1/8 x 1/8 square notch 60-80 sq.ft./gal.	U.R.A., 2000	U.R.A., EW, 2000	U.R.A., EW, 2000
Ceramic Tile 1/4 x 1/4 x 1/4 square notch 30-40 sq. ft./gal.	460	460	460

*Typical trowel sizes recommended for these flooring products. Please refer to AAT's Specification Sheet and labels for specific recommendations.